

SELECTABLE GALLONAGE NOZZLES

1" 362-Series Selectable Gallonage Nozzle

- 12-23-30 GPM (50-90-115 LPM)
- Optional 1-1/2" inlet size
- Compatible with Low and Medium Expansion Foam Tube Style 210 & 225 (see page 34)
- Can be used for high pressure applications up to 580 psi (40 bar)

362 1" Selectable Gallonage Nozzle with Pistol Grip

362-TO 1" Selectable Gallonage Nozzle Tip Only

- Twist shutoff optional

362-BC 1" Selectable Gallonage Nozzle with Pistol Grip

- Brass construction

362-BCTO 1" Selectable Gallonage Nozzle Tip Only

- Brass construction



Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
362	1" (25mm)	7.4" (190mm)	2.3 (1.1kg)	12-23-30	50-90-115
362-TO	1" (25mm)	5.5" (140mm)	1.6 (0.7kg)	12-23-30	50-90-115
362-BC	1" (25mm)	7.4" (190mm)	5.3 (2.4kg)	12-23-30	50-90-115
362-BCTO	1" (25mm)	5.5" (140mm)	3.3 (1.5kg)	12-23-30	50-90-115

1-1/2" 366-Series Selectable Gallonage Nozzles

- 30-60-95-125 GPM (115-230-360-475 LPM)
- Optional 2-1/2" inlet size
- 100 psi (7 bar) standard, 75 psi (5 & 6 bar) optional
- Compatible with Low and Medium Expansion Foam Tube Style 212, 213 & 226 (see page 34)

366 1-1/2" Selectable Gallonage Nozzle with Pistol Grip

366-TO 1-1/2" Selectable Gallonage Nozzle Tip Only

- Twist shutoff optional

366-BA 1-1/2" Selectable Gallonage Breakapart Nozzle

- Combination of Style 366-TO tip and Style 101 shutoff (see page 35)

366-BC 1-1/2" Selectable Gallonage Nozzle with Pistol Grip

- Brass construction

366-BCTO 1-1/2" Selectable Gallonage Nozzle with Pistol Grip

- Brass construction



Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
366	1-1/2" (38mm)	9" (228mm)	3.9 (1.7kg)	30-60-95-125	115-230-360-475
366-TO	1-1/2" (38mm)	6.3" (160mm)	2.2 (1kg)	30-60-95-125	115-230-360-475
366-BA	1-1/2" (38mm)	12.4" (315mm)	4.4 (2kg)	30-60-95-125	115-230-360-475
366-BC	1-1/2" (38mm)	9" (228mm)	8.3 (3.7kg)	30-60-95-125	115-230-360-475
366-BCTO	1-1/2" (38mm)	6.3" (160mm)	5.5 (2.5kg)	30-60-95-125	115-230-360-475

