

# SELECTABLE GALLONAGE NOZZLES

## Wide-Range 369-Series Selectable Gallonage Nozzles

- 30-60-95-125-150-200 GPM (115-230-360-475-550-750 LPM)
- 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Compatible with Low and Medium Expansion Foam Tube Style 214, 215 & 227 (see page 34)



Style 369

**369** Wide-Range Selectable Gallonage Nozzle with Pistol Grip

**369-TO** Wide-Range Selectable Gallonage Nozzle Tip Only

**369-BA** Wide-Range Selectable Gallonage Breakapart Nozzle  
 • Combination of Style 369-TO tip and Style 102 shutoff (see page 35)



Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
369	1-1/2" (38mm)	10.2" (260mm)	5.7 (2.6kg)	30-60-95-125-150-200	115-230-360-475-550-750
369-TO	1-1/2" (38mm)	7" (178mm)	3.3 (1.5kg)	30-60-95-125-150-200	115-230-360-475-550-750
369-BA	1-1/2" (38mm)	13" (330mm)	6.2 (2.8kg)	30-60-95-125-150-200	115-230-360-475-550-750

## High-Range 368-Series Selectable Gallonage Nozzles

- 95-125-150-200-250 GPM (360-475-550-750-950 LPM)
- 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Compatible with Low and Medium Expansion Foam Tube Style 214, 215 & 227 (see page 34)



Style 368-TO



Style 368

**368** High-Range Selectable Gallonage Nozzle with Pistol Grip

**368-TO** High-Range Selectable Gallonage Nozzle Tip Only

**368-BA** High-Range Selectable Gallonage Breakapart Nozzle  
 • Combination of Style 368-TO tip and Style 102 shutoff (see page 35)

**368-BC** High-Range Selectable Gallonage Nozzle with Pistol Grip  
 • Brass construction



Style 368-BA

**368-BCTO** High-Range Selectable Gallonage Nozzle Tip Only  
 • Brass construction

Style 368-BC

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
368	2-1/2" (65mm)	11" (280mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950
368-TO	1-1/2" (38mm)	7.1" (180mm)	3.2 (1.5kg)	95-125-150-200-250	360-475-550-750-950
368-BA	2-1/2" (65mm)	13" (330mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950
368-BC	2-1/2" (65mm)	11" (280mm)	14.7 (6.7kg)	95-125-150-200-250	360-475-550-750-950
368-BCTO	1-1/2" (38mm)	7.1" (180mm)	9.9 (4.5kg)	95-125-150-200-250	360-475-550-750-950

