

SELECTABLE GALLONAGE NOZZLES

1-1/2" 366-Series Selectable Gallonage Nozzles

- 30-60-95-125 GPM (115-230-360-475 LPM)
- 100 psi (7 bar) standard, 75 psi (5 & 6 bar) optional
- Compatible with Foam Tube Style 213 (see page 24)

366 1-1/2" Selectable Gallonage Nozzle with Pistol Grip

366-TO 1-1/2" Selectable Gallonage Nozzle Tip Only

- Twist shutoff optional

366-BA 1-1/2" Selectable Gallonage Breakapart Nozzle

- Combination of Style 366-TO tip and Style 101 shutoff (see page 25)

366-BC 1-1/2" Selectable Gallonage Nozzle with Pistol Grip

- Brass construction

366-BI Selectable Gallonage Nozzle with Integrated 2-1/2" Inst. Male

- BIM inlet



Style 366-TO



Style 366



Style 366-BA



Style 366-BC



Style 366-BI

1-1/2" 370-Series Selectable Gallonage Nozzles

370 1-1/2" Selectable Gallonage Nozzle with Pistol Grip

- 75-100-125-150 GPM (280-380-475-570 LPM)
- 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Compatible with Foam Tube Style 215 (see page 24)



Style 370



Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
366	1-1/2" (38mm)	9" (228mm)	3.9 (1.7kg)	30-60-95-125	115-230-360-475
366-TO	1-1/2" (38mm)	6.3" (160mm)	2.2 (1kg)	30-60-95-125	115-230-360-475
366-BA	1-1/2" (38mm)	12.4" (315mm)	4.4 (2kg)	30-60-95-125	115-230-360-475
366-BC	1-1/2" (38mm)	9" (228mm)	8.3 (3.7kg)	30-60-95-125	115-230-360-475
366-BI	2-1/2" (65mm)	12.6" (320mm)	4.4 (2kg)	30-60-95-125	115-230-360-475
370	1-1/2" (38mm)	9" (228mm)	3.9 (1.8kg)	75-100-125-150	280-380-475-570