

EN SELECTABLE GALLONAGE NOZZLES

- EN 15182-2 Type 3 and DIN 14367 compliant
- Combination pattern nozzles with multiple flow settings for operator flow control
- Produce straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Easy to operate with a-quarter turn from straight stream to fog
- One-click turn of the moulded bumper ring to flashover pattern position
- Raised lug on the bumper for flashover fog pattern
- Maximum flow position touch button on the flow selection control ring
- Exceptionally lightweight and compact
- Stainless steel spinning teeth ensure corrosion resistance and durability
- Newly improved handle with two reinforced metal pieces to improve durability
- Heavy-duty chrome plated shutoff ball ensures smooth action and long-lasting service life
- Ergonomic design pistol grip for comfort
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Compatible with Protek's foam aeration tubes



Style 2360 & 2361



Style 2365 & 2366



Style 2368

EN SELECTABLE GALLONAGE NOZZLES



Style 2368-TP



Raised lug for flashover fog pattern



Newly improved handle with two reinforced metal pieces on each side to prevent breakage

Specification

Style	Inlet Size	Length	Weight	Flow Settings	
				LPM	Pressure
2360	1" BSP F	19cm	1.2kg	20-40-100-150	6 bar
2361	1" BSP F	19cm	1.2kg	50-100-150-230	6 bar
2365	1.5" BSP F	21.5cm	1.6kg	70-130-230-400	6 bar
2366	1.5" BSP F BS 336 Inst.	22.8cm	1.6kg	100-250-350-500	6 bar
2368	2.5" BSP F BS 336 Inst.	27.9cm	2.5kg	285-500-600-800-950	6 bar
2368-TP	2.5" BSP F BS 336 Inst.	43.1cm	4.2kg	285-500-600-800-950	6 bar