

# AUTOMATIC NOZZLES



## Style 311, 312, 314, 314-TP

- Automatically adjusts to fluctuating water flow to maintain effective pressure and a consistent stream in all flow ranges
- Extensive range of flow settings
- Excellent performance at pressure as low as 50 psi (3.5 bar)
- Exceptionally lightweight, compact and corrosion resistant alloy construction
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Ball valve control with stainless steel spinning teeth
- Suitable for foam application and compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray, Nozzles, Shutoff and Tips)



Style 311



Style 312



Style 314



Style 314-TP

Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				GPM	LPM
<b>311</b>	1-1/2" (38mm)	9.2" (234mm)	3.7 (1.7)	60-125	230-475
<b>312</b>	1-1/2" (38mm)	10.6" (269mm)	5.6 (2.5)	60-200	230-750
<b>314</b>	2-1/2" (65mm)	12.2" (309mm)	8 (3.6)	75-325	285-1325
<b>314-TP</b>	2-1/2" (65mm)	17.1" (435mm)	9.9 (4.5)	75-325	285-1325