

# CONSTANT GALLONAGE NOZZLES

## 1" 371-Series Constant Gallonage Nozzle

- 371, 371-BC 1" Constant Gallonage Nozzle with Pistol Grip**
- 13, 25, 40 or 60 GPM (50, 100, 150 or 230 LPM)
  - Optional 1-1/2" inlet size
  - 100 psi (7 bar) standard, 85 psi (6 bar) optional
  - Compatible with Foam Tube Style 211 (see page 34)

**371-TO 1" Constant Gallonage Nozzle Tip Only**

**371-BCTO 1" Constant Gallonage Nozzle Tip Only**

- Brass construction



Style 371

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
371	1" (25mm)	7.1" (180mm)	2.1 (0.9kg)	13, 25, 40 or 60	50, 100, 150 or 230
371-BC	1" (25mm)	7.1" (180mm)	5.3 (2.4kg)	13, 25, 40 or 60	50, 100, 150 or 230

## 1-1/2" 372-Series Constant Gallonage Nozzles

- 60, 95 or 125 GPM (230, 360 or 475 LPM)
- Optional 2-1/2" inlet size
- Flow setting at 100 psi (7 bar) operating pressure
- Compatible with Foam Tube Style 212 (see page 34)

**372 1-1/2" Constant Gallonage Nozzle with Pistol Grip**

**372-TO 1-1/2" Constant Gallonage Nozzle Tip Only**

**372-BA 1-1/2" Constant Gallonage Breakapart Nozzle**

- Combination of Style 372-TO tip and Style 101 shutoff (see page 35)

**372-BC 1-1/2" Constant Gallonage Nozzle with Pistol Grip**

- Industrial nozzle
- Brass construction

**372-BCTO 1-1/2" Constant Gallonage Nozzle Tip Only**

- Brass construction



Style 372



Style 372-BC



Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
372	1-1/2" (38mm)	8.5" (216mm)	3.6 (1.6kg)	60, 95 or 125	230, 360 or 475
372-TO	1-1/2" (38mm)	5.9" (150mm)	1.9 (0.8kg)	60, 95 or 125	230, 360 or 475
372-BA	1-1/2" (38mm)	12" (305mm)	4.2 (1.9kg)	60, 95 or 125	230, 360 or 475
372-BC	1-1/2" (38mm)	8.5" (216mm)	7.5 (3.4kg)	60, 95 or 125	230, 360 or 475
372-BCTO	1-1/2" (38mm)	5.9" (150mm)	5.1 (2.3kg)	60, 95 or 125	230, 360 or 475

