

Industrial Nozzle

Style 373-BC

- Corrosion resistant brass construction ideal for marine, offshore production rigs, industrial and other corrosive environments
- Effectively produces a constant gallonage from straight stream to full fog
- Combines quality stream performance at various pressures with the simplicity of a fixed orifice
- Custom flow and pressure combinations are available on request, delivered with a calibrated flow disc installed
- Tough, durable design that is easy to operate
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)



Specification

Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				LPM	GPM
373-BC	1-1/2" or 2-1/2" (38mm or 65mm)	9.8" (249mm)	12.7 (5.8kg)	150, 175 or 200	550, 660 or 750

Industrial Nozzle

Unique Features On Peorwk Industrial Nozzles

Flow pattern detents facilitate positive positioning and smooth action

Laser-etched anodized label for excellent durability and visibility

Unique series number for easy identification

New and improved handle design

Fixed moulded teeth or stainless steel spinning teeth

Stainless filter mesh prevents blockage caused by debris

Constant flow regardless of pattern change

Choice of 1-1/2" NH or 2-1/2" BIM inlet

Flow rate etched on the baffle on request
Can be field retrofitted to optional flows and pressures

Style 373-BC

Ergonomic design pistol grip (available in various colours)

Heavy-duty chrome plated metal shutoff ball for smooth action and long life

