

# CONSTANT GALLONAGE NOZZLE



## Style 373-SV

- Effectively produces a constant gallonage from straight stream to full fog
- Slide valve design delivers adjustable flow rates via the handle
- Combines quality stream performance at various pressure with the simplicity of a fixed orifice
- Custom flow and pressure combinations are available on request, delivered with a calibrated flow disc installed
- Affordable priced, easy to use and reliable in tough situations
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Excellent performance at pressure as low as 50 psi (3.5 bar)
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Available in tip only and shutoff combinations
- Compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)

## Specification

Style	Inlet Size	Length	Weight Lbs	Flow Settings	
				GPM	LPM
373-SV	1-1/2" (38mm)	11.8" (300mm)	5.4 (2.46kg)	150,175 or 200	550, 660 or 750



# CONSTANT GALLONAGE NOZZLE



## Unique Features On Protek Nozzles



Fixed moulded teeth or stainless steel spinning teeth

Flow pattern detents facilitate positioning and smooth action

Laser-etched anodized label for excellent durability and visibility

Unique series number for easy identification

New and improved handle design

Constant flow regardless of pattern change

Stainless filter mesh prevents blockage caused by debris

Flow rate etched on the baffle on request  
Can be field retrofitted to optional flows and pressures

Choice of 1-1/2" NH or 2-1/2" BIM inlet

### Style 373-SV

Slide valve design controls multiple flow settings



Ergonomic design pistol grip (available in various colours)



[www.protektfire.com.tw](http://www.protektfire.com.tw) ♦ [sales@protektfire.com.tw](mailto:sales@protektfire.com.tw)