

Industrial Nozzle

Style 374-BC



- Corrosion resistant brass construction ideal for marine, offshore production rigs, industrial and other corrosive environments
- Effectively produces a constant gallonage from straight stream to full fog
- Combines quality stream performance at various pressures with the simplicity of a fixed orifice
- Custom flow and pressure combinations are available on request, delivered with a calibrated flow disc installed
- Tough, durable design that is easy to operate
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Available in tip only and shutoff/playpipe combinations
- Compatible with protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)

Specification

Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				LPM	GPM
374-BC	2-1/2"(65mm)	11"(279mm)	14.7(6.7kg)	150, 175, 200 or 250	550, 660, 750 or 950

Industrial Nozzle

Unique Features On Peorwk Industrial Nozzles

Flow pattern detents facilitate positive positioning and smooth action

Laser-etched anodized label for excellent durability and visibility

Unique series number for easy identification

New and improved handle design


Stainless filter mesh prevents blockage caused by debris

Choice of 2-1/2" NH or 2-1/2" BIM inlet

Style 374-BC

Ergonomic design pistol grip (available in various colours)

Heavy-duty chrome plated metal shutoff ball for smooth action and long life



Fixed moulded teeth or stainless steel spinning teeth

Constant flow regardless of pattern change

Flow rate etched on the baffle on request
Can be field retrofitted to optional flows and pressures

