

# CONSTANT GALLONAGE NOZZLES

## Mid-Range 374-Series Constant Gallonage Nozzles

**374-TP** Mid-Range Constant Gallonage Nozzle with Playpipe

**374-BCTP** Mid-Range Constant Gallonage Nozzle with Playpipe

- Industrial nozzle
- Brass construction



Style 374-TP



Style 374-BCTP

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
374-TP	2-1/2" (65mm)	16.7" (424mm)	9.5 (4.3kg)	150, 175, 200 or 250	550, 660, 750 or 950
374-BCTP	2-1/2" (65mm)	17" (432mm)	21 (9.5kg)	150, 175, 200 or 250	550, 660, 750 or 950

## High-Range 375-Series Constant Gallonage Nozzle

**375** High-Range Constant Gallonage Nozzle with Pistol Grip

- 200, 250, 300 or 350 GPM (750, 950, 1140 or 1325 LPM)
- Flow setting at 100 psi (7 bar) operating pressure
- Compatible with Foam Tube Style 217 (see page 34)



Style 375

**375-TO** High-Range Constant Gallonage Nozzle Tip Only

- Varying flow settings with an easy turn of the baffle
- Flow rates are etched on the baffle
- Optional 1-1/2" or 2-1/2" inlet size
- Can be used as an attachment to Protek monitors  
Style 611, 600-1 and 600-2



Style 375-TO

1.5" inlet

2.5" inlet

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
375	2-1/2" (65mm)	11.8" (300mm)	7.5 (3.4kg)	200, 250, 300 or 350	750, 950, 1140 or 1325
375-TO	1-1/2" (38mm)	8.8" (223mm)	5.1 (2.3kg)	200, 250, 300 or 350	750, 950, 1140 or 1325
	2-1/2" (65mm)	9.5" (240mm)	5.7 (2.6kg)		

