

Low-Pressure Selectable Gallonage Nozzle



- Combination pattern nozzle with five versatile flow rate settings up to 150 GPM (570 LPM) at a low operating pressure of 5 bar (75 PSI)
- Effectively minimises pressure on pumps and fire fighter fatigue whilst delivering more water
- Slide valve design reduces turbulence and controls flow rate whilst preserving perfect quality stream
- Change in the flow pattern (from fog to jet) can readily be achieved via an efficient 120-degree turn of the moulded bumper
- Enhanced positivity of the flow selection ring delivers optimal stream performance and effective operating control
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Lightweight hardcoat anodized aluminum construction
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)



Specification

Style	Inlet Size	Length	Weight LBS (kg)	Flow Rate at 75 PSI (5 BAR)	
				GPM	LPM
355	1-1/2" (38mm)	11.2" (284mm)	5.3 (2.4 kg)	30-60-95-125-150	115-230-360-475-570

Low-Pressure Selectable Gallonage Nozzle



- Versatile multiple flow rate settings up to 150 GPM (570 LPM) at a reduced working pressure of 5 bar (75 PSI)
- Slide valve design reduces turbulence and controls flow rate whilst preserving perfect quality stream
- Efficient 120-degree turn of the moulded bumper from jet stream to fog pattern
- Improved positivity of flow selection ring ensures optimal stream performance
- Large index ring with indicator allows easy flow, pressure or flush selections with a gloved hand
- Optimal straight stream and fog pattern performance are achieved at the selected flow and the single rated pressure
- Integral inlet screen prevents debris from entering nozzle and affecting stream quality