

# 361-FORCE LOW PRESSURE NOZZLE

## Style 361-F



- Combination pattern nozzle with four versatile flow rate settings up to 60 GPM (230 LPM) at a low operating pressure of 5 bar (75 PSI)
- Effectively minimizes pressure on pumps and fire fighter fatigue whilst delivering more water
- Change in the flow pattern (from fog to jet) can readily be achieved via an effective 120° turn of the moulded bumper
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Enhanced positivity of the flow selection ring and ball-valve shut off delivers optimal stream performance and effective operating control
- Available in either lightweight hardcoat anodized aluminium or corrosion resistant brass construction
- Available in tip only and shutoff combinations
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Standard NH inlet or optional BIM / Machino / Storz inlets
- Compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)

### Specification

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings @5 bar (75 PSI)	
				GPM	LPM
361-F	1" (25mm)	7.3" (186 mm)	2.3 (1.05 kg)	13-25-40-60	50-100-150-230

# 361-FORCE LOW PRESSURE NOZZLE

## Unique Features On Protek Nozzles

