

# Marine & Industrial Nozzle

## Style 372-BC

- Corrosion resistant brass construction ideal for marine, offshore production rigs, industrial and other corrosive environments
- Meets the stringent performance requirements of the US Coast Guard
- Effectively produces a constant gallonage from straight stream to full fog
- Combines quality stream performance at various pressures with the simplicity of a fixed orifice
- Custom flow and pressure combinations are available on request, delivered with a calibrated flow disc installed
- Tough, durable design that is easy to operate
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Ideal for AFFF applications and compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)



## Specification

Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				LPM	GPM
372-BC	1-1/2"(38mm)	8.5"(216mm)	7.5(3.4kg)	60,95 or 125	230, 360 or 475

# Marine & Industrial Nozzle

## Unique Features On Peorwk Industrial Nozzles



Flow pattern detents facilitate positive positioning and smooth action

Laser-etched anodized label for excellent durability and visibility

Unique series number for easy identification

New and improved handle design

Stainless filter mesh prevents blockage caused by debris

Choice of 1-1/2" NH or 2-1/2" BIM inlet

Fixed moulded teeth or stainless steel spinning teeth

Constant flow regardless of pattern change

Flow rate etched on the baffle on request  
Can be field retrofitted to optional flows and pressures

### Style 372-BC

Ergonomic design pistol grip (available in various colours)

Heavy-duty chrome plated metal shutoff ball for smooth action and long life

