

INDUSTRIAL MONITOR



Style 648

- Full 3-1/4" waterway for flow rate up to 1250 GPM (4800 LPM)
- Cast-in turning vanes for efficient flow and minimal friction loss.
- Full 360° rotation.
- Vertical travel of 135° from 90 ° above and 45° below horizontal.
- Positive friction locks with brass knob for both horizontal and vertical travel to hold desired position.
- Maximum operating pressure up to 16 bar.
- Stainless steel lever for durability and easy control.



| Compatible Protek's Nozzles | | | | | | | | | | |
|-----------------------------|--------|-----|-----|--------|--------|--------|--------|--------|--------|--------|
| 823 | 825 | 830 | 832 | 845 | 846 | 847 | 848 | 887 | 888 | 889 |
| 823-BC | 825-BC | | | 845-BC | 846-BC | 847-BC | 848-BC | 887-BC | 888-BC | 889-BC |

Style 648 monitors shown with Style 835-BC nozzle



| Style 648 | | | | |
|----------------|------|--------------------|--------|---------------|
| Max. GPM (LPM) | | 1250 (4800) | | |
| Inlet | Size | 3" | 4" | 3" |
| | Type | Flange | Flange | Female Thread |
| Outlet | | 2-1/2" | | |
| Control | | Tiller Bar | | |
| Material | | Brass | | |
| Finish | | Red Powder Coating | | |
| Friction | | 18 psi at 1250 GPM | | |
| | | 15 psi at 1000 GPM | | |
| Travel | | 135° Vertical | | |
| | | 360° Rotation | | |
| Weight | | 52 Lbs (23.5 kg) | | |