

Industrial Monitor

Style 660

Unique Features of Protek Industrial Monitors

- 1 Flow turning vanes in each elbow efficiently reduce friction
- 2 Powder coating produces a tough, corrosion resistant finish
- 3 Positive friction locks with brass knob for both horizontal and vertical travel to hold desired position
- 4 Stainless steel lever for durability and easy control
- 5 Major components made from brass alloy (UNS C83600, ASTM B62) for a long-lasting Service life
- 6 Optional flanges : ANSI, ASA, DIN or ISO
- 7 Double-row stainless steel ball bearings in monitor joints ensure smooth movements even when the monitor is under pressure
- 8 Compatible with Protek's diverse range of monitor nozzles and smooth bore tips for various applications

Style 660 monitor shown with
Style 109 stream shaper and
Style 121 Quad Stacked Tips



Industrial Monitor

Style 660

- Corrosion resistant brass construction ideal for marine, offshore, industrial and other corrosive environments
- Full 4" waterway for flow rate of up to 2000 GPM (7570 LPM)
- Cast-in turning vanes for efficient flow
- Full 360° rotation
- Vertical travel of 135° from 90° above and 45° below horizontal
- Positive friction locks with brass knob for both horizontal and vertical travel to hold desired position
- Operating pressure of 200 psi (14 bar)
- Stainless steel lever for durability and easy control



Specification

| Style 660 | | | | |
|----------------|-------------|--------|---------------|-----------------------------------|
| Max. GPM (LPM) | 2000 (7570) | | Finish | Red Powder Coating |
| Inlet | Size | 4" | Friction Loss | 38 psi at 2000 gpm |
| | Type | Flange | | 15 psi at 1200 gpm |
| Outlet | 3-1/2" | | Travel | 135° Vertical |
| Control | Tiller Bar | | | 360° Rotation |
| Material | Brass | | Weight | 99 lbs (45 kg) to 110 lbs (50 kg) |

Compatible Products



837-BC
Monitor Nozzle



833
Automatic Nozzle



109
Stream Shaper



121
Quad Stacked Tips

