

MONITOR ACCESSORIES

Monitor Accessories

560 Monitor Ball-Valve Shutoff

- High quality brass body
- Accomodates a wide range of Protek monitors
- Improved sealing and increased gating ability



Style 560

	Style 560
Max. GPM (LPM)	1800 GPM (6800)
Inlet Flange	3", 4" ANSI or 3" NPT
Outlet Flange	3", 4" ANSI or 3" NPT
Waterway	3"
Operating Pressure	Min. 50 psi (3.5 bar) Max. 250 psi (17 bar)
Weight	54 lbs. (24.5 kg)



Style 560 valve shown with Style 649 monitor

699 Hydrant Mount

- Allows a fixed site monitor to be mounted to a 2-1/2" (65 mm) hydrant port
- Height adjustment from the ground to centre of the hydrant discharge is 17-1/2" (445 mm) to 28" (712 mm)
- Length is 9-1/2" from the swivel to the middle of the flange
- 2-1/2" swivel inlet
- 3" or 4" ANSI outlet flange
- Maximum operating pressure 100 psi (7 bar)
- Maximum flow 1200 gpm (4500 lpm)

Style	Weight (lbs)	Inlet	Outlet
699	40	2-1/2" swivel	3" or 4" Flange



Style 699

