

MONITOR ACCESSORIES

Monitor Accessories

560 Monitor Ball-Valve Shutoff

- High quality brass body
- Accomodates a wide range of Protek monitors
- Improved sealing and increased gating ability



Style 560

| | Style 560 |
|---------------------------|--|
| Max. GPM (LPM) | 1800 GPM (6800) |
| Inlet Flange | 3", 4" ANSI or 3" NPT |
| Outlet Flange | 3", 4" ANSI or 3" NPT |
| Waterway | 3" |
| Operating Pressure | Min. 50 psi (3.5 bar) Max. 250 psi (17 bar) |
| Weight | 54 lbs. (24.5 kg) |



Style 560 valve shown with Style 649 monitor

699 Hydrant Mount

- Allows a fixed site monitor to be mounted to a 2-1/2" (65 mm) hydrant port
- Height adjustment from the ground to centre of the hydrant discharge is 17-1/2" (445 mm) to 28" (712 mm)
- Length is 9-1/2" from the swivel to the middle of the flange
- 2-1/2" swivel inlet
- 3" or 4" ANSI outlet flange
- Maximum operating pressure 100 psi (7 bar)
- Maximum flow 1200 gpm (4500 lpm)

| Style | Weight (lbs) | Inlet | Outlet |
|-------|--------------|---------------|-----------------|
| 699 | 40 | 2-1/2" swivel | 3" or 4" Flange |



Style 699

